TEST REPORT

Prepared for:

[redacted]

[redacted]

Product Name:	**Retractable Safety Gate**
Model No.:	**BPM-SG71-WHT**
Trade Mark:	**N/A**
Date of Test:	**From October 10, 2025 to October 27, 2025**
Date of Report:	**October 27, 2025**
Report Number:	**HK25101011105-1RR**

Prepared by:

Shenzhen HUAK Testing Technology Co., Ltd.

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.

Applicant:	[redacted]
Address:	[redacted]
Manufacturer:	**BABY PROOF ME**
Address:	[redacted]

The following sample was submitted and identified by/on behalf of the client as:

Sample Name:	Retractable Safety Gate
Model No.:	BPM-SG71-WHT
Trade Mark:	N/A
Labeled Age Grading:	6-24 months
Requested Age Grading:	6-24 months
Age Group Assessed As Per Age Guideline:	6-24 months
Age Group Applied in Testing:	6-24 months
Sample Receiving Date:	October 10, 2025
Testing Period:	From October 10, 2025 to October 27, 2025
Results:	Please refer to next page(s).

****

Signed for and on behalf of HUAK

Approved by: Jason Zhou

Lab Manager

REPORT CERTIFICATION HUAK TESTING APPROVAL

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.

Summary of Test Results:

	TEST REQUEST	CONCLUSION
A	As specified in title 16, code of federal regulations, chapter II- consumer products safety commission of U.S.A	
	1. 16CFR 1500.50.51.52.53 Simulating use and abuse of toys	PASS
	2. 16CFR 1501 Small Objects	PASS
	3. 16CFR 1500.48 Sharp point	PASS
	4. 16CFR 1500.49 Sharp edge	PASS
B	16CFR PART 1239 - SAFETY STANDARD FOR GATES AND ENCLOSURES & ASTM F1004-23 Standard Consumer Safety Specification for Expansion Gates and Expandable Enclosures	PASS
C	ASTM F963-23 Standard Consumer Safety Specification for Toy Safety	
	1. -Mechanical and Physical Tests	PASS
	4.2 Flammability	PASS
	4.3 Toxicology	PASS
	3. -Section 4.3.5.1 Heavy Metals Content in Paint and Similar Surface-coating Materials	PASS
	4. -Section 4.3.5.2 Heavy Metals Content in Toy Substrate Materials	PASS
D	- USA 16CFR Part 1303 Ban of Lead Containing Paint and Certain Consumer Products Bearing Lead- Containing Paint	PASS
E	- USA Consumer Product Safety Improvement Act (CPSIA) Sec.101 Children´s products containing Lead; Lead paint rule - CPSIA section 101(a)(2)-Lead in accessible substrate materials and 15 U.S.C. § 1278a Lead in Children's products	PASS
F	- USA Consumer Product Safety Improvement Act (CPSIA) Sec.108 Prohibition on sale of certain products containing specified phthalates - USA 16CFR Part 1307 Prohibition of Children's Toys and Child Care Articles Containing Specified Phthalates	PASS
G	- CPSA Section 14(a) (5) Tracking Labels for Children's Products (15 USC §2063(a)(5) (CPSA))	PASS
H	16CFR PART 1130 – REQUIREMENTS FOR CONSUMER REGISTRATION OF DURABLE INFANT OR TODDLER PRODUCTS	PASS

****

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Results:

A. As specified in title 16, code of federal regulations, chapter II- consumer products Safety commission of U.S.A

Applicable Section	Description	Result
16CFR 1500.50.51.52.53	Normal use testing	Pass
	Abuse testing	
	Impact test	Pass
	Bite test	NA
	Flexure test	NA
	Torque test (53e)	Pass
	Tension test (53f)	Pass
	Compression test(53g)	Pass
16CFR 1501	Identifying toys and other articles intended for use by Children under 3 years of age which present choking, aspiration, or ingestion hazards because of small parts.	Pass
16CFR 1500.48	Technical requirements for determining a sharp point in toys and other articles intended for use by children under 8 years of age.	Pass
16CFR 1500.49	Technical requirements for determining a sharp metal or glass edge in toys and other articles intended for use by children under 8 years of age.	Pass

--NA= Not Applicable

****

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.

B. 16CFR PART 1239 - SAFETY STANDARD FOR GATES AND ENCLOSURES&
ASTM F1004-23 Standard Consumer Safety Specification for Expansion Gates and Expandable Enclosures

Applicable Section	Description	Result
§ 1239.1	Scope This part establishes a consumer product safety standard for gates and enclosures.	
§ 1239.2	Requirements for gates and enclosures. Each gate and enclosure must comply with all applicable provisions of ASTM F1004-22, Standard Consumer Safety Specification for Expansion Gates and Expandable Enclosures, approved on June 1, 2022. The Director of the Federal Register approves this incorporation by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. A read-only copy of the standard is available for viewing on the ASTM website at https://www.astm.org/READINGLIBRARY/. You may obtain a copy from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959; telephone (610) 832-9585; www.astm.org. You may inspect a copy at the Office of the Secretary, U.S. Consumer Product Safety Commission, 4330 East West Highway, Bethesda, MD 20814, telephone (301) 504-7479, email cpsc-os@cpsc.gov, or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, email fr.inspection@nara.gov, or go to: www.archives.gov/federal-register/cfr/ibr-locations.html.	

Applicable Section	Description	Result
1	Scope 1.1 This consumer safety specification covers minimum safety performance requirements, test methods, and requirements for labeling and instructional material to minimize hazards to young children resulting from the normal use and reasonably foreseeable misuse and abuse of expansion gates and expandable enclosures. 1.2 Products known as expansion gates and expandable enclosures, or by any other name, which are in the scope of this consumer safety specification are intended for young children aged six months through 24 months, and are defined in Section 3. 1.3 Expansion gates and expandable enclosures defined in Section 3 are for domestic use and are not to be confused with other types of gates or enclosures that may be specifically designed for commercial, institutional, agricultural, pet use, or any other such use. 1.4 No expansion gate or expandable enclosure as defined in Section 3, that is, produced after the approval date of this consumer safety specification either by label or other means, shall indicate compliance with this specification unless it conforms to all the requirements contained herein. 1.5 For expediency, expansion gates and expandable enclosures as defined in Section 3 will heretofore be referred to in this consumer safety specification as “gates” and “enclosures” unless referred to definitively. 1.6 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard. 1.7 The following pertains only to the test methods portion, Section 7, of this specification. This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use. 1.8 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
2	Referenced Documents	
3	Terminology	
4	Calibration and Standardization	
5	General Requirements	
5.1	Wood Parts	NA
5.2	Screws shall not be used in the assembly of any components or locking or attaching device(or devices)that are intended to be removed by the contractor	Pass
5.3	There shall be no hazardous sharp edges or points as defined by 16 CFR 1500.48 and 16 CFR 1500.49 before or after testing to this consumer safety specification.	Pass
5.4	There shall be no small parts as defined by 16 CFR 1501 before testing or liberated as a result of testing to this specification.	Pass
5.5	Openings—Holes or slots that extend entirely through a wall section of any rigid material less than 0.375 in. (9.53 mm) thick and admit a 0.210-in. (5.33-mm) diameter rod shall also admit a 0.375-in. (9.53-mm) diameter rod. Holes or slots that are between 0.210 in. (5.33 mm) and 0.375 in. (9.53 mm) and have a wall thickness less than 0.375 in. (9.53 mm) but are limited in depth to 0.375 in. (9.53 mm) maximum by another rigid surface shall be permissible (see Fig. 1). The product shall be evaluated in all manufacturer's recommended positions.	NA
5.5.1	Openings through multiple wall sections and openings created by multiple wall sections must meet the size requirements in 5.5 if the total thickness of the combined wall sections and any air gap between the wall sections is less than 0.375 in. (9.53 mm).	NA
5.6	Exposed Coil Springs- Any exposed coil spring, which is accessible to the occupant having or capable of generating a space between coils of 0.210 in. (5.33 mm) or greater during static load testing in accordance with 7.8 shall be covered or otherwise designed to prevent injury from entrapment.	NA
5.7	Scissoring, Shearing, and Pinching- -The gate/expandable enclosure when in the manufacturer's recommended use position(s) shall be designed and constructed to prevent injury to the child from any scissoring, shearing, or pinching when members or components rotate about a common axis or fastening point, slide, pivot, fold, or otherwise move relative to one another. Scissoring, shearing, or pinching that may cause injury shall not be permissible when the edges of any rigid parts admit a probe greater than 0.210 in. (5.33 mm) and less than 0.375 in. (9.53 mm) diameter at any accessible point through the range of motion of such parts.	Pass
5.8	Labeling	Pass
5.8.1	Warning labels (whether paper or nonpaper) shall be permanent when tested in accordance with 7.12.1 - 7.12.3.	Pass
5.8.2	Warning statements applied directly onto the surface of the product by hot stamping, heat transfer, printing, wood burning, etc, shall be permanent when tested in accordance with 7.12.4.	NA
5.8.3	Nonpaper labels shall not liberate small parts when tested in accordance with 7.12.5	NA
5.9	The paint and surface coating on the product shall comply with 16 CFR 1303.	Pass
5.10	Protective Components If a child can grasp protective components, such as caps, sleeves, or plugs used	Pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
	for protection from sharp edges, points, or entrapment of fingers or toes, between the thumb and forefinger, or teeth, or if there is at least a 0.040 in. (1.00 mm) gap between the component and its adjacent parent component, such components shall not be removed when tested in accordance with 7.7.	
6	Performance Requirements	
6.1	The following performance requirements apply to gates and enclosures when they are erected or installed in and of the manufacturers recommended use positions	Pass
6.1.1	Completely-bounded Opening	Pass
6.1.2	Height of Sides (not be less than 22 in. (560 mm))	Pass
6.1.3	Vertical strength	Pass
6.1.4	Bottom Spacing	Pass
6.1.5	Configuration of Upper most Edge	Pass
6.2	Latching/Locking and Hinge Mechanisms:	Pass
6.2.1	Pressure-Mounted Gates	NA
6.2.2	Units with Egress Panels	Pass
6.2.2.1	Automatic Closing Systems	NA
6.3	Horizontal Push-Out	Pass
6.3.1	All gates shall be tested in accordance with 7.9. At each test location, the average push-out force shall exceed 30lbf (133 N). In addition, each individual force shall exceed 20lbf (89 N).	Pass
6.4	Locking Device	Pass
6.4.1	Each single-action locking or latching device shall require a minimum force of 10lbf (45 N) to activate the release mechanism when tested in accordance with 7.6.	NA
6.4.2	The locking or latching device shall be a double action release mechanism. There are no force requirements for double-action locking or latching devices.	Pass
6.5	Toys	NA
6.6	Slat Strength Test	NA
6.7	Pressure -Mounted Gate-Mounting Hardware - Installation components (for example, wall cups) that are necessary for the gate to meet the performance requirements in 6.3.1 shall be included with the gate in one of the following ways:	Pass
(a)	Temporarily affixed to a main panel of the gate with the warning in 8.5.7 similarly attached.	Pass
(b)	Temporarily attached to each of the pressure pads/ tension bolt pads of the gate.	Pass
(c)	Not affixed or attached to the gate as long as the gate is designed in such a way that does not allow for its installation without the mounting hardware.	Pass
6.8	Visual Side-pressure Indicators- Any pressure- mounted gate that does not require the use of pressure-mounted gate mounting hardware per 6.7 to meet the performance requirements in 6.3.1 shall include visual side-pressure indicators.	NA
6.8.1	Visual side-pressure indicators shall be conspicuous and readily identifiable to a person installing and standing near the gate	NA
6.8.2	Visual side-pressure indicators shall monitor pressure for each point of contact with the mounting surface utilizing one or more of the following three options.	NA

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
	Such indicators, when the gate is tested in accordance with 7.9, shall indicate when the required side pressure has been attained upon installation of the gate and continue to display the side pressure status while the gate is in a manufacturer's recommend use position.	
6.8.2.1	A single visual side-pressure indicator for each individual contact point.	NA
6.8.2.2	A single visual side-pressure indicator for each individual rail (top and bottom), so the opposing horizontal contact points are addressed.	NA
6.8.2.3	A single visual side-pressure indicator for the entire gate.	NA
7	Test Methods	
8	Marking and labeling	Pass
9	Instructional Literature	Pass

-- NA = Not Applicable

****

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.

C.1 ASTM F963-23 Standard Consumer Safety Specification for Toy Safety -Mechanical and Physical Tests

Applicable Section	Description	Result
4	Safety Requirements	
4.1	Material Quality	Pass
4.2	Flammability	Pass
4.3	Toxicology	Refer to Chemical section
4.3.1	Hazardous Substances	NA
4.3.2	Manufacturing and Packaging of Food	NA
4.3.3	Indirect Food Additives	NA
4.3.4	Cosmetics	NA
4.3.5	Heavy Elements	Pass
4.3.6	Cosmetics, Liquids, Pastes, Putties, Gels, Powders, and Items of Avian Feather Origin	NA
4.3.7	Stuffing Materials	NA
4.3.8	Phthalates	Pass (See E)
4.4	Electrical/Thermal Energy—Toys operating from nominal 120-V branch circuits shall conform to 16 CFR 1505, issued under the FHSA.	NA
4.5	Sound-producing Toys	NA
4.6	Small Objects	Pass
4.6.1	Toys that are intended for children under 36 months of age are subject to the requirements of 16 CFR 1501.	Pass
4.6.2	Mouth-actuated Toys	NA
4.6.3	Toys and games intended for use by children under 3 years (36 months) to 6 years (72 months) must comply with small parts labeling requirements (small parts Warnings)	NA
4.7	Accessible Edges	Pass
4.8	Projections	NA
4.9	Accessible Points	Pass
4.10	Wires or Rods	NA
4.11	Nails and Fasteners	Pass
4.12	Plastic Film	NA
4.13	Folding Mechanisms and Hinges	NA
4.14	Cords, Straps, and Elastics	NA
4.15	Stability and Over-load Requirements	NA
4.16	Confined Spaces	NA
4.17	Wheels, Tires, and Axles	NA
4.18	Holes, Clearance, and Accessibility of Mechanisms	Pass
4.19	Simulated Protective Devices (such as helmets, hats, and goggles)	NA

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
4.19.1	Eye Protection—All rigid toys that cover the face, such as goggles, space helmets, or face shields, shall be constructed of impact-resistant material that will not have sharp edges, sharp points, or loose parts that could enter the eye before or after being tested in accordance with 8.5 – 8.10. This applies to items with cutout eye holes as well as items that cover the eyes.	NA
4.19.2	Toys that simulate safety protective devices (examples include, but are not limited to, construction helmets and sports helmets) and their packages shall be labeled clearly in accordance with 5.9 to warn the purchaser that they are not safety protective devices.	NA
4.20	Pacifiers	NA
4.21	Projectile Toys	NA
4.22	Teethers and Teething Toys	NA
4.23	Rattles	NA
4.24	Squeeze Toys	NA
4.25	Battery-operated Toys	NA
4.26	Toys Intended to be Attached to a Crib or Playpen	NA
4.27	Stuffed and Beanbag-type Toys	NA
4.28	Stroller and Carriage Toys	NA
4.29	Art Materials	NA
4.30	Toy Gun Marking	NA
4.31	Balloons	NA
4.32	Certain Toys with Nearly Spherical Ends	NA
4.33	Marbles	NA
4.34	Balls	NA
4.35	Pompoms	NA
4.36	Hemispheric-Shaped Objects	NA
4.37	Yo Yo Elastic Tether Toys	NA
4.38	Magnets	NA
4.39	Jaw Entrapment in Handles and Steering Wheels	NA
4.40	Expanding Materials	NA
4.41	Toy Chests	NA
5	Labeling Requirements	
5.1	Federal Government Requirements	Pass
5.1.2	Tracking Label	Pass
5.2	Age Grading Labeling	Pass
5.3	Safety Labeling Requirements	Pass
5.4	Aquatic Toys	NA

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
5.5	Crib and Playpen Toys	NA
5.6	Mobiles	NA
5.7	Stroller and Carriage Toys	NA
5.8	Toys Intended to be Assembled By an Adult	Pass
5.9	Simulated Protective Devices	NA
5.10	Toys with Functional Sharp Edges or Points	NA
5.11	Small Objects, Small Balls, Marbles, and Balloons	NA
5.12	Art Materials—Toys and components of toys that fall within the definition of art material as found in 16 CFR 1500.14(b)(8) shall be labeled in accordance with the provisions of that section and Practice D4236.	NA
5.13	Electric Toys—Refer to 16 CFR 1505.3 for required labeling.	NA
5.14	Battery-operated Toys	NA
5.15	Promotional Materials	NA
5.16	Magnets	NA
6	Instructional Literature	
6.1	Definition and Description	Pass
6.2	Crib and Playpen Toys	NA
6.3	Mobiles	NA
6.4	Toys Intended to be Assembled By an Adult	Pass
6.5	Battery-Operated Toys	NA
6.6	Battery-powered Ride-on Toys	NA
6.7	Toys in Contact with Food	NA
6.8	Toys Chests	NA
6.9	The instructional material for toys which require a manufacturer-supplied specialty or custom tool to access the battery(ies) shall direct caregivers to retain the tool for future use, to store it where the child cannot access it, and state that the tool is not a toy.	NA
7	Producer's Markings	
7.1	Either a principal component of a toy or the package of a toy shall be marked with the name and address of the producer or the distributor.	Pass
7.2	Battery-powered Ride-on Toys	NA
7.3	Toy chests	NA

--NA= Not Applicable

--NR = Not Requested

****

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.

Use and abuse testing:

Applicable Section	Description		Age Group	Test condition	Result
8.5	Normal use testing		--		Pass
8.6	Abuse testing		--		Pass
8.7	Impact test	8.7.1 Drop Test	0 to 18	10 × 4.5 ft ± 0.5 in. (137 cm)	Pass
			over 18 to 36	4 × 3.0 ft ± 0.5 in. (91 cm)	NA
			over 36 to 96	4 × 3.0 ft ± 0.5 in. (91 cm)	NA
		8.7.2 Tipover Test for Large, Bulky Toys			NA
		8.7.3 Tumble Test for Wheeled Toys			NA
		8.7.4 Impact Test for Toys that Cover the Face			NA
8.8	Torque test				Pass
8.9	Tension test				Pass
8.10	Compression test				Pass
8.11	Tests for Tire Removal and Snap-in Wheel and Axle Assembly Removal				NA
8.12	Flexure Test				NA
8.13	Test Methods for Mouth-actuated Toys and Mouth actuated Projectile Toys				NA
8.14	Projectiles				NA
8.15	Test for Stability of Ride-on Toys or Toy Seats				NA
8.23	Test for Loops and Cords				NA

C.2 Section 4.2 Flammability Tests

(A5) FLAMMABILITY TESTING PROCEDURE FOR SOLIDS AND SOFT TOYS

Flammability test of material

Sample	Burn rate (in/sec.)	Result
White plastic	DNI	Pass

Note: In accordance with the ASTMF963, the burning rate should not be greater than 0.1inch per second.

DNI =Did Not Ignited SE= Self-Extinguished IBE= Ignite but Extinguished

Remark:

A5.2.2 soft toy—any stuffed or plush toy, that may or may not be parts or components of other toys.
A5.2.3 solids—toys or toy parts constructed of rigid, flexible, or pliable solids.
A5.2.4 accessories—an item intended to be removed to enhance the play pattern.
A5.2.5 strings—long slender flexible material usually consisting of several strands (as of thread or yarn) woven or twisted together, usually used to bind, fasten, tether, or tie.
A5.2.6 paper—Examples of paper products are traditional playing cards, newspaper, magazines, and construction paper.
A5.3 Exemptions
A5.3.1 Strings, paper, and ping-pong balls. /A5.3.2 Accessible components having a major dimension of 1in. (25 mm) or less. /A5.3.5 Packaging materials intended to be discarded by the consumer.

****

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Tested part(s):

Seq. no	Part(s) name	Sample description
1	White plastic	White safety door side fixed plastic
2	Transparent double-sided adhesive	White security door double-sided adhesive
3	White coating	White safety gate pole
4	White plastic mesh	White safety net
5	Transparent plastic	With ring suction cup base
6	Silver metal	Metal ring with ring suction cup
7	White plastic black, orange print	White security door warning label
8	Silver metal	Long screw
9	Grey plastic	Grey expansion screw
10	White plastic	White expansion screw
11	Silver metal	Small screw
12	Silver metal	White safety door side fixing screw
13	Black plastic	Black safety door side fixed plastic
14	Black plastic mesh	Black security door net
15	Black coating	Black safety door pole
16	Grey plastic	Gray safety door side fixed plastic
17	Grey plastic mesh	Gray safety door net
18	Grey coating (R)	Gray safety door pole
19	Silver metal	Silver metal expansion screw
20	Silver metal	screw

(R)=Re-submitted sample.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

C.3 Section 4.3.5.1 Heavy Metals content in paint and similar surface coating material

(1) Total Lead Content

Test method: With reference to ASTM F963-23 Section 8.3.1, sample was digested with acid mixture and analyzed by inductively coupled plasma atomic emission spectrometer (ICP-OES).

Item	Unit	MDL	Results			Limit(Each)
			3	15	18	
Lead Content (Pb)	mg/kg	2	62	N.D.	N.D.	90
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

(2) Soluble Heavy Metals Content

Test method: With reference to ASTM F963-23 Section 8.3.2. The heavy metals content was determined by inductively Coupled plasma atomic emission spectrometer (ICP-OES).

Item	Unit	MDL	Results			Limit
			3	15	18	
Soluble Lead (Pb)	mg/kg	2	N.D.	N.D.	N.D.	90
Soluble Antimony (Sb)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Arsenic (As)	mg/kg	2	N.D.	N.D.	N.D.	25
Soluble Barium (Ba)	mg/kg	2	415	386	319	1000
Soluble Cadmium (Cd)	mg/kg	2	N.D.	N.D.	N.D.	75
Soluble Chromium (Cr)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Mercury (Hg)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Selenium (Se)	mg/kg	2	N.D.	N.D.	N.D.	500
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

C.4 Section 4.3.5.2 Heavy Metals Content in Toy Substrate Materials

(1) Total Lead Content

Test method: With reference to ASTM F963-23 Section 8.3.1, sample was digested with acid mixture and analyzed by inductively coupled plasma atomic emission spectrometer (ICP-OES).

Item	Unit	MDL	Results			Limit(Each)
			1+13+16	2	4+14+17	
Lead Content (Pb)	mg/kg	2	N.D.	N.D.	N.D.	100
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit(Each)
			5	7	9	
Lead Content (Pb)	mg/kg	2	N.D.	N.D.	N.D.	100
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit(Each)
			10	/	/	
Lead Content (Pb)	mg/kg	2	N.D.	/	/	100
Conclusion	/	/	**Pass**	/	/	/

(2) Soluble Heavy Metals Content

Test method: With reference to ASTM F963-23 Section 8.3.5. The heavy metals content was determined by inductively Coupled plasma atomic emission spectrometer (ICP-OES).

Item	Unit	MDL	Results			Limit
			1	2	4	
Soluble Lead (Pb)	mg/kg	2	N.D.	N.D.	N.D.	90
Soluble Antimony (Sb)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Arsenic (As)	mg/kg	2	N.D.	N.D.	N.D.	25
Soluble Barium (Ba)	mg/kg	2	50	N.D.	N.D.	1000
Soluble Cadmium (Cd)	mg/kg	2	N.D.	N.D.	N.D.	75
Soluble Chromium (Cr)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Mercury (Hg)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Selenium (Se)	mg/kg	2	N.D.	N.D.	N.D.	500
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Item	Unit	MDL	Results			Limit
			5	7	9	
Soluble Lead (Pb)	mg/kg	2	N.D.	N.D.	N.D.	90
Soluble Antimony (Sb)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Arsenic (As)	mg/kg	2	N.D.	N.D.	N.D.	25
Soluble Barium (Ba)	mg/kg	2	N.D.	N.D.	N.D.	1000
Soluble Cadmium (Cd)	mg/kg	2	N.D.	N.D.	N.D.	75
Soluble Chromium (Cr)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Mercury (Hg)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Selenium (Se)	mg/kg	2	N.D.	N.D.	N.D.	500
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit
			10	13	14	
Soluble Lead (Pb)	mg/kg	2	N.D.	N.D.	N.D.	90
Soluble Antimony (Sb)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Arsenic (As)	mg/kg	2	N.D.	N.D.	N.D.	25
Soluble Barium (Ba)	mg/kg	2	N.D.	10	N.D.	1000
Soluble Cadmium (Cd)	mg/kg	2	N.D.	N.D.	N.D.	75
Soluble Chromium (Cr)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Mercury (Hg)	mg/kg	2	N.D.	N.D.	N.D.	60
Soluble Selenium (Se)	mg/kg	2	N.D.	N.D.	N.D.	500
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit
			16	17	/	
Soluble Lead (Pb)	mg/kg	2	N.D.	N.D.	/	90
Soluble Antimony (Sb)	mg/kg	2	N.D.	N.D.	/	60
Soluble Arsenic (As)	mg/kg	2	N.D.	N.D.	/	25
Soluble Barium (Ba)	mg/kg	2	49	N.D.	/	1000
Soluble Cadmium (Cd)	mg/kg	2	N.D.	N.D.	/	75
Soluble Chromium (Cr)	mg/kg	2	N.D.	N.D.	/	60
Soluble Mercury (Hg)	mg/kg	2	N.D.	N.D.	/	60
Soluble Selenium (Se)	mg/kg	2	N.D.	N.D.	/	500
Conclusion	/	/	**Pass**	**Pass**	/	/

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Remark:
Maximum acceptable element migration from toy materials

Toy material	Element (mg/kg)							
	Sb	As	Ba	Cd	Cr	Pb	Hg	Se
Surface Coatings and Substrates Other Than Modeling Clay Included as Part of a Toy	60	25	1000	75	60	90	60	500
Modelling Clays Included as Part of a Toy	60	25	250	50	25	90	25	500

D. USA 16 CFR Part 1303 Ban of Lead Containing Paint and Certain Consumer Products Bearing Lead- Containing Paint

Test method: With reference to CPSC-CH-E1003-09.1, sample was digested with acid mixture and analyzed by inductively coupled plasma atomic emission spectrometer (ICP-OES)

Item	Unit	MDL	Results			Limit(Each)
			3	15	18	
Lead Content (Pb)	mg/kg	2	62	N.D.	N.D.	90
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

E. USA Consumer Product Safety Improvement Act (CPSIA) Sec.101 Children´s products containing lead; lead paint rule

(1) Substrate Materials

Test method: With reference to CPSC-CH-E1001-08.3; CPSC-CH-E1002-08.3, by acid digestion and analysis was performed by inductively coupled plasma atomic emission spectrometer (ICP-OES).

Item	Unit	MDL	Results			Limit(Each)
			1+13+16	2	4+14+17	
Lead Content (Pb)	mg/kg	2	N.D.	N.D.	N.D.	100
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit(Each)
			5	7	9	
Lead Content (Pb)	mg/kg	2	N.D.	N.D.	N.D.	100
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit(Each)
			10	6	8	
Lead Content (Pb)	mg/kg	2	N.D.	21	30	100
Conclusion	/	/	**Pass**	/	/	/

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Item	Unit	MDL	Results			Limit(Each)
			11	12	19	
Lead Content (Pb)	mg/kg	2	28	N.D.	N.D.	100
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit(Each)
			20	/	/	
Lead Content (Pb)	mg/kg	2	N.D.	/	/	100
Conclusion	/	/	**Pass**	/	/	/

(2) Paint and similar surface coating material

Test method: With reference to CPSC-CH-E1003-09.1, sample was digested with acid mixture and analyzed by inductively coupled plasma atomic emission spectrometer (ICP-OES)

Item	Unit	MDL	Results			Limit(Each)
			3	15	18	
Lead Content (Pb)	mg/kg	2	62	N.D.	N.D.	90
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

F. USA Consumer Product Safety Improvement Act (CPSIA) Sec.108 Prohibition on sale of certain products containing specified phthalates
USA 16CFR Part 1307 Prohibition of Children's Toys and Child Care Articles Containing Specified Phthalates
Test method: With reference to CPSC-CH-C1001-09.4, by solvent extraction and analysis was performed by gas chromatographic-mass spectrometer (GC-MS).

Item	Unit	MDL	Results			Limit(Each)
			1+13+16	2	4+14+17	
Dibutyl Phthalate (DBP)	mg/kg	30	N.D.	N.D.	N.D.	1000
Benzylbutyl Phthalate (BBP)	mg/kg	30	N.D.	N.D.	N.D.	1000
Bis-(2-ethylhexyl) Phthalate (DEHP)	mg/kg	30	N.D.	N.D.	158	1000
Diisononyl Phthalate (DINP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Di-isobutyl Phthalate (DIBP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Dicyclohexyl Phthalate (DCHP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Di-n-hexyl Phthalate (DHEXP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Di-n-pentyl Phthalates (DPENP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Item	Unit	MDL	Results			Limit(Each)
			5	7	9	
Dibutyl Phthalate (DBP)	mg/kg	30	N.D.	N.D.	N.D.	1000
Benzylbutyl Phthalate (BBP)	mg/kg	30	N.D.	N.D.	N.D.	1000
Bis-(2-ethylhexyl) Phthalate (DEHP)	mg/kg	30	N.D.	N.D.	N.D.	1000
Diisononyl Phthalate (DINP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Di-isobutyl Phthalate (DIBP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Dicyclohexyl Phthalate (DCHP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Di-n-hexyl Phthalate (DHEXP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Di-n-pentyl Phthalates (DPENP)	mg/kg	100	N.D.	N.D.	N.D.	1000
Conclusion	/	/	**Pass**	**Pass**	**Pass**	/

Item	Unit	MDL	Results			Limit(Each)
			10	3+15+18	/	
Dibutyl Phthalate (DBP)	mg/kg	30	N.D.	N.D.	/	1000
Benzylbutyl Phthalate (BBP)	mg/kg	30	N.D.	N.D.	/	1000
Bis-(2-ethylhexyl) Phthalate (DEHP)	mg/kg	30	N.D.	N.D.	/	1000
Diisononyl Phthalate (DINP)	mg/kg	100	N.D.	N.D.	/	1000
Di-isobutyl Phthalate (DIBP)	mg/kg	100	N.D.	N.D.	/	1000
Dicyclohexyl Phthalate (DCHP)	mg/kg	100	N.D.	N.D.	/	1000
Di-n-hexyl Phthalate (DHEXP)	mg/kg	100	N.D.	N.D.	/	1000
Di-n-pentyl Phthalates (DPENP)	mg/kg	100	N.D.	N.D.	/	1000
Conclusion	/	/	**Pass**	**Pass**	/	/

Note:

- N.D. =Not Detected or less than MDL.
- MDL=Method Detection Limit.
- NA= Not Applicable
- %=Percentage by weight.
- 0.1%=1000mg/kg, mg/kg=ppm.
- "+"=The test result is obtained from composite testing on materials linked with "+" mark, it is possible that individual test result can be higher if materials are tested separately. This had been taken in account in the conclusion of this report.

****

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

G. CPSA Section 14(a) (5) Tracking Labels for Children's Products (15 USC §2063(a)(5) (CPSA))

Applicable Section	Description	Result
(a)(5) (A)	Effective 1 year after the date of enactment of the Consumer Product Safety Improvement Act of 2008, the manufacturer of a children's product shall place permanent, distinguishing marks on the product and its packaging, to the extent practicable, that will enable—	Pass
(i)	the manufacturer to ascertain the location and date of production of the product, cohort information (including the batch, run number, or other identifying characteristic), and any other information determined by the manufacturer to facilitate ascertaining the specific source of the product by reference to those marks; and	Pass
(ii)	the ultimate purchaser to ascertain the manufacturer or private labeler, location and date of production of the product, and cohort information (including the batch, run number, or other identifying characteristic).	Pass
(B)	The Commission may, by regulation, exclude a specific product or class of products from the requirements in subparagraph (A) if the Commission determines that it is not practicable for such product or class of products to bear the marks required by such subparagraph. The Commission may establish alternative requirements for any product or class of products excluded under the preceding sentence consistent with the purposes described in clauses (i) and (ii) of subparagraph (A).	NA
(b)	The Commission may by rule prescribe reasonable testing programs for any product which is subject to a consumer product safety rule under this Act, or a similar rule, regulation, standard, or ban under any other Act enforced by the Commission, and for which a certificate is required under subsection (a). Any test or testing program on the basis of which a certificate is issued under subsection (a) may, at the option of the person required to certify the product, be conducted by an independent third party qualified to perform such tests, unless the Commission, by rule, requires testing by an independent third party for a particular rule, regulation, standard, or ban, or for a particular class of products.	Pass
(c)	The Commission may by rule require the use and prescribe the form and content of labels which contain the following information (or that portion of it specified in the rule) —	Pass
(1)	The date and place of manufacture of any consumer product.	Pass
(2)	The cohort information (including the batch, run number, or other identifying characteristic) of the product.	Pass
(3)	A suitable identification of the manufacturer of the consumer product, unless the product bears a private label in which case it shall identify the private labeler and shall also contain a code mark which will permit the seller of such product to identify the manufacturer thereof to the purchaser upon his request.	Pass
(4)	In the case of a consumer product subject to a consumer product safety rule, a certification that the product meets all applicable consumer product safety standards and a specification of the standards which are applicable. Such labels, where practicable, may be required by the Commission to be permanently marked on or affixed to any such consumer product. The Commission may, in appropriate cases, permit information required under paragraphs (1) and (2) of this subsection to be coded.	Pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
(d)	REQUIREMENT FOR ADVERTISEMENTS.—No advertisement for a consumer product or label or packaging of such product may contain a reference to a consumer product safety rule or a voluntary consumer product safety standard unless such product conforms with the applicable safety requirements of such rule or standard.	Pass
(e)	WITHDRAWAL OF ACCREDITATION-	Pass
(f)	DEFINITIONS.--In this section	Pass
(g)	REQUIREMENTS FOR CERTIFICATES.-- (1) IDENTIFICATION OF ISSUER AND CONFORMITY ASSESSMENT BODY.--Every certificate required under this section shall identify the manufacturer or private labeler issuing the certificate and any third party conformity assessment body on whose testing the certificate depends. The certificate shall include, at a minimum, the date and place of manufacture, the date and place where the product was tested, each party's name, full mailing address, telephone number, and contact information for the individual responsible for maintaining records of test results.	Pass
(h)	RULE OF CONSTRUCTION.	Pass
(i)	ADDITIONAL REGULATIONS FOR THIRD PARTY TESTING	Pass

****

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

H. Standards and consumer registration of durable nursery products – "CPSIA Sec.104 (d)/ CPSC 16CFR 1130-Requirements for consumer registration of durable infant or toddler products

Applicable Section	Description	Result
§ 1130.1	Purpose, scope, and effective date	
(a)	Purpose. This part prescribes a consumer product safety rule establishing requirements for consumer registration of durable infant or toddler products. These requirements are intended to improve the effectiveness of recalls of, and safety alerts regarding, such products.	
(b)	Scope. Part 1130 applies to manufacturers, including importers, of durable infant or toddler products, as defined in § 1130.2(a). It does not apply to infant or child restraint systems intended for use in automobiles that are covered by the registration program of the National Highway Traffic and Safety Administration (NHTSA) at 49 CFR 571.213, or to products that comprise a travel system, and are sold with a child restraint system that is covered by the NHTSA registration program at 49 CFR 571.213.	
(c)	Compliance Date. Compliance with this part 1130 shall be required on June 28, 2010 for the following products: full-size cribs and nonfull-size cribs; toddler beds; high chairs, booster chairs, and hook-on chairs; bath seats; gates and other enclosures for confining a child; play yards; stationary activity centers; infant carriers; strollers; walkers; swings; and bassinets and cradles. Compliance with this part 1130 shall be required on December 29, 2010 for the following products: Children's folding chairs, changing tables, infant bouncers, infant bath tubs, bed rails and infant slings. Compliance with this part 1130 shall be required on September 24, 2020 for contoured changing pads (a type of baby changing product). The rule shall apply to durable infant or toddler products, as defined in § 1130.2(a), that are manufactured on or after those dates.	
§ 1130.2	Definitions. In addition to the definitions given in section 3 of the Consumer Product Safety Act (15 U.S.C. 2052), the following definitions apply:	
(a)	Definition of durable infant or toddler product means the following products intended for use, or that may be reasonably expected to be used, by children under the age of 5 years. The listed product categories are further defined in the applicable standards that the Commission issues under section 104(b) of the Consumer Product Safety Improvement Act of 2008, and include products that are combinations of the following product categories:	
(1)	Full-size cribs and non-full-size cribs;	NA
(2)	Toddler beds;	NA
(3)	High chairs, booster seats, and hook-on chairs;	NA
(4)	Bath seats;	NA
(5)	Gates and other enclosures for confining a child;	Pass
(6)	Play yards;	NA
(7)	Stationary activity centers;	NA
(8)	Infant carrier, including soft infant and toddler carriers, hand-held infant carriers, sling carriers, and frame child carriers;	NA
(9)	Strollers;	NA
(10)	Walkers;	NA
(11)	Swings;	NA
(12)	Bassinets and cradles, including bedside sleepers;	NA

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
(13)	Children's folding chairs and children's folding stools;	NA
(14)	Baby changing products;	NA
(15)	Infant bouncers;	NA
(16)	Infant bathtubs;	NA
(17)	Bed rails;	NA
(b)	Manufacturer, for purposes of this part, in the case of a product produced within the United States, means the domestic manufacturer of the product, and in the case of an imported product, means the importer of the product.	Pass
(c)	Product recall means action taken pursuant to sections 12, 15(c) or 15(d) of the CPSA (15 U.S.C. 2061, 2054(c), or 2064(d)), and action taken pursuant to a corrective action plan implemented by a company in cooperation with the Commission, where the firm is conducting one or more of the following: repair of the product; replacement of the product; or refund of the purchase price of the product.	Pass
(d)	Safety alert means notice or warning of a potential problem with an individual product or class of products so that consumers and other users of the affected products respond accordingly to reduce or eliminate the potential for injury.	Pass
§ 1130.3	General requirements.	
(a)	Each manufacturer of a durable infant or toddler product shall:	Pass
(1)	Provide consumers with a postage-paid consumer registration form that meets the requirements of this part 1130 with each such product;	Pass
(2)	Maintain a record in accordance with the requirements set forth in § 1130.8 of the contact information (names, addresses, e-mail addresses, and telephone numbers) of consumers who register their products with the manufacturer under this part 1130;	Pass
(3)	Permanently place the manufacturer name and contact information, model name and number, and the date of manufacture on each durable infant or toddler product in accordance with the requirements set forth in § 1130.4.	Pass
(b)	Consumer information collected by a manufacturer pursuant to the requirements of this part 1130 shall not be used by the manufacturer, nor disseminated by the manufacturer to any other party, for any purpose other than notification to such consumer in the event of a product recall or safety alert.	Pass
§ 1130.4	Identification on the product.	
(a)	Each durable infant or toddler product shall be permanently marked with the manufacturer name, and contact information (U.S. address and telephone number, toll free if available) model name and number, and date of manufacture.	Pass
(1)	If the manufacturer regularly uses only a model name or a model number, but not both, to identify the product, he/she may provide only the model name or number rather than creating a model name or number for the sole purpose of this part 1130.	Pass
(2)	If the manufacturer regularly identifies the product by a product identification number ("PIN") or other similar identifying number rather than a model number, he/she may provide that identifying number instead of a model number.	Pass
(3)	The date referred to in paragraph (a) of this section shall include the month and year of manufacture and can be stated in code.	Pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
(4)	A permanent mark is one that can reasonably be expected to remain on the product during the useful life of the product.	Pass
(b)	The information required by this section shall be in English, legible, and in a location that is conspicuous to the consumer.	Pass
(c)	The information required by this section may be combined with other information marked on the product.	Pass
§ 1130.5	Requirements for registration forms.	
(a)	Comply with the format and text requirements set forth in § 1130.6 as shown in figures 1 and 2 of this part;	Pass
(b)	State all information required by this part 1130 in the English language;	Pass
(c)	Be attached to the surface of each durable infant or toddler product so that, as a practical matter, the consumer must notice and handle the form after purchasing the product;	Pass
(d)	Include the manufacturer's name, model name and number for the product, and the date of manufacture;	Pass
(e)	Include an option for consumers to register through the Internet;	Pass
(f)	Include the statement required in § 1130.6(c)(1) that information provided by the consumer shall not be used for any purpose other than to facilitate a recall of or safety alert regarding that product.	Pass
§ 1130.6	Requirements for format and text of registration forms.	
(a)	Size of form. The form shall be at least the size of two standard post cards, connected with perforation for later separation, so that each of the two portions is at least 3½ inches high x 5 inches wide x 0.007 inches thick.	Pass
(b)	Layout of form	Pass
(1)	General. The form shall consist of four parts: top and bottom, divided by perforations for easy separation, and front and back.	Pass
(2)	Font size and typeface. The registration form shall use bold black typeface. The size of the type shall be at least 0.12 in (3.0 mm) for the purpose statement required in paragraph (c)(1) of this section, and no less than 0.10 in (2.5 mm) for the other information in the registration form. The title of the purpose statement and the retention statement required in paragraph (d)(2) of this section shall be in all capitals. All other information shall be in capital and lowercase type.	Pass
(c)	Front of form	Pass
(1)	Top front of form: Purpose statement. The top portion of the front of each form shall state: "PRODUCT REGISTRATION FOR SAFETY ALERT OR RECALL ONLY. We will use the information provided on this card to contact you only if there is a safety alert or recall for this product. We will not sell, rent, or share your personal information. To register your product, please complete and mail the bottom part of this card, or visit our online registration at: www.Web sitename.com." Manufacturers that do not have a Web site may provide an email address and state at the end of the purpose statement: "To register your product, please complete and mail the bottom part of this card, or email your contact information, the model name and number, and date of manufacture of the product, as provided on this card, to: name@firmname.com."	Pass
(2)	Bottom front of form: Manufacturer's mailing address. The bottom portion of the front of each form shall be pre-addressed and postage-paid with the manufacturer's name and mailing address where registration information is to be	Pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
	collected. A manufacturer may list a brand name in addition to the manufacturer's name. If a manufacturer uses a third party to process registration forms, the third party's name may be included as a "c/o" ("in care of") in the address on the form.	
(d)	Back of the form	Pass
(1)	Top back of form	Pass
(i)	Product information and manufacturer's identification. The top portion of the back of each form shall state: "Manufacturer's Contact Information" and provide the manufacturer's name and contact information (a U.S. mailing address displayed in sentence format, Web site address, a telephone number, toll-free, if available); product model name and number (or other identifier as described in § 1130.4(a)(1) and (2)); and manufacture date of the product. A rectangular box shall be placed around the model name, model number, and manufacture date. A manufacturer may list the brand name in addition to the manufacturer's name.	Pass
(ii)	Retention statement. On the back of each form, just above the perforation line, the form shall state: "KEEP THIS TOP PART FOR YOUR RECORDS. FILL OUT AND RETURN BOTTOM PART."	Pass
(2)	Bottom back of form	Pass
(i)	Consumer information. The bottom portion of the back of each form shall have blocks for the consumer to provide his/her name, address, telephone number, and email address. These blocks shall be 5 mm wide and 7 mm high, with as many blocks as possible to fill the width of the card allowing for normal printing practices.	Pass
(ii)	Product information. The following product information shall be provided on the bottom portion of the back of each form below the blocks for consumer information printed directly on the form or on a pre-printed label that is applied to the form: the model name and number (or other identifier as described in § 1130.4(a)(1) and (2)), and the date of manufacture of the product. A rectangular box shall be placed around the model name, model number, and manufacture date. A manufacturer may include its name on the bottom portion of the back of the form if they choose to do so.	Pass
§ 1130.7	Requirements for Web site registration or alternative e-mail registration.	
(a)	Link to registration page. The manufacturer's Web site, or other Web site established for the purpose of registration under this part 1130, shall be designed with a link clearly identified on the main web page that goes directly to "Product Registration."	Pass
(b)	Purpose statement. The registration page shall have the following statement at the top of the page: "PRODUCT REGISTRATION FOR SAFETY ALERT OR RECALL ONLY. We will use the information provided on this page only to contact you if there is a safety alert or recall for this product. We will not sell, rent, or share your personal information. If you register on this Web site you do not need to fill out the card that came with your product."	Pass
(c)	Content of registration page. The Web site registration page shall request only the consumer's name, address, telephone number, e-mail address, product model name and number, and the date of manufacture. The consumer's telephone number and e-mail address shall not be required for the consumer to submit the registration form. No other information shall appear on the electronic registration form, except for identification of the manufacturer or a link to the manufacturer's home page, a field to confirm submission, and a prompt to	Pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Applicable Section	Description	Result
	indicate any incomplete or invalid fields before submission. Accessing the electronic registration form shall not cause additional screens or electronic banners to appear.	
(d)	Alternative for manufacturers without a Web site. A manufacturer that lacks a Web site shall provide for consumers to register their product through e-mail. Such e-mail addresses shall be set up to provide an automatic reply to confirm receipt of the consumer's registration information	Pass
§ 1130.8	Recordkeeping and notification requirements.	
(a)	Each manufacturer of a durable infant or toddler product shall maintain a record of registrants for each product manufactured that includes all of the information provided by each consumer registered.	Pass
(b)	Each manufacturer of a durable infant or toddler product shall use the information provided by the registrant to notify the registrant in the event of a voluntary or involuntary recall of, or safety alert regarding, such product.	Pass
(c)	Each manufacturer of a durable infant or toddler product shall maintain a record of the information provided by the registrant for a period of not less than 6 years after the date of manufacture of the product.	Pass
(d)	Records required under this section shall be made available within 24 hours, upon the request of any officer, employee, or agent acting on behalf of the U.S. Consumer Product Safety Commission.	Pass
(e)	Optional barcode.	Pass
(1)	A manufacturer may include a barcode, or other machine readable data, that when scanned would provide a direct link for the consumer to register the product.	Pass
(2)	Such a link must comply with all the requirements of this part 1130, including those in § 1130.7 and the restriction that the manufacturer shall not use or disseminate the consumer registration information for any purpose other than notifying the consumer of a safety alert or recall.	Pass

--NA= Not Applicable

****

**** Modified History ****

Revision	Description	Issued Date	Remark
Revision 1.0	Initial Test Report Release	2025/10/27	Jason Zhou

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Photograph of Sample





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.





HUAK authenticate the photo on original report only

***** End of Report *****

Remark: This report is considered invalidated without the Special Seal for Inspection of the HUAK. This report shall not be altered, increased or deleted. The results shown on this test report refer only to the sample(s) tested unless otherwise stated, under the conditions agreed upon. Anyone who uses this report should understand all of the details of the engagement. Without written approval of HUAK, this test report shall not be copied except in full and published as advertisement.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannont be reproduced except in full with our prior written permission.